

# LED BUILD TO ORDER

## LED POST TOP FIXTURES



### GS02 SERIES



- NEW CCT tunable from 3000K - 4000K - 5000K .
- Adjustable head for ease of shipment and installation.
- Black, white or bronze housing options.
- 35~150 watt model options.
- Slip fitter base provides easy installation options.

SPECIFICATIONS	
BEAM ANGLE	Type II 120°
CERTIFICATIONS	cULus
CRI	>80
DIMMABLE	1-10V
LED TYPE	SMD2835 [0.5W]
INPUT VOLTAGE	100-277V; 50/60Hz
OPERATING TEMP	-40°F~122°F
POWER FACTOR	>0.9
THD	≤20%
WARRANTY	5 Years
WATERPROOF	IP65 Wet Location

### QUICK SHIP STOCK ORDERING

MODEL	WATTAGE	LUMENS	BASE	COLOR TEMP	WEIGHT (Net   Gross)	DIMENSIONS
GLL-GS02-35WFAT2F1-abcd	35 Watt	4,060~4,830LM	Slip Fitter	Tunable	9.5 lbs   11.9 lbs	15" Dia x 20.7"H
GLL-GS02-55WFAT2F1-abcd	55 Watt	6,215~7,150LM	Slip Fitter	Tunable	8.8 lbs   12.13 lbs	15" Dia x 20.7"H
GLL-GS02-75WFAT2F1-abcd	75 Watt	8,625~10,125LM	Slip Fitter	Tunable	10.4 lbs   12.8 lbs	15" Dia x 20.7"H
GLL-GS02-100WFAT2F1-abcd	100 Watt	11,800~12,800LM	Slip Fitter	Tunable	14.3 lbs   18.74 lbs	17.7" Dia x 23.6"H
GLL-GS02-150WFAT2F1-abcd	150 Watt	17,700~19,200LM	Slip Fitter	Tunable	14.3 lbs   18.74 lbs	17.7" Dia x 23.6"H

**ORDERING GUIDE & EXAMPLE FOR STOCK INVENTORY: GLL-GS02-75WFAT2F1-BRSP [75 Watt | Bronze Housing | Surge | Photocell]**

GLL = Green Lighting LED | GS02 = Product Series | Wattage | F = FAHOLD Driver | A = Hongli Diodes | T2 = Viewing Optics | F1 = Version Number |  
 [a] housing color = [BH] black, [WH] white or [BR] bronze | [b] motion sensor = blank no motion or [MS] motion sensor |  
 [c] surge protector = blank no surge protector or [S] 10kv Surge Protector | [d] photocell = blank no photocell or [P] photocell