



LED QUICK SHIP PROGRAM

LED CORN | POST TOP LAMPS



SURGE PROTECTION



ENCLOSED FIXTURE



RATED

DAMP

LOCATION



RATED



CLW08 SERIES



SPECIFICATIONS	
BEAM ANGLE	360°
CERTIFICATIONS	cULus, DLC
CRI	>80
LED TYPE	Lumileds SMD2835
INPUT VOLTAGE	100-277V; 50/60Hz
OPERATING TEMP	-40°F~122°F
POWER FACTOR	>0.9
SURGE PROTECTION	Yes
THD	≤20%
WARRANTY	6 Years
WATERPROOF	IP64 Damp Location
WIRING	Direct Wire Only

- Direct wire installation. Must bypass ballast.
- Enclosed fixture rated. IP64 damp location.
- 4KV surge protection ≤75 watt. 6KV surge protection ≥100 watt.
- 27 watt & 36 watt E26 base only; 45 watt & 54 watt both E26 and EX39; 75watt and up EX39 only.
- DLC & cULus listed.
- Standard, clear lens lamp 140 lm/watt efficacy.
- DLC tested inside enclosed fixture at 115 lm/watt.

QUICK SHIP STOCK ORDERING

MODEL	WATTAGE	LUMENS	BASE	COLOR TEMP	WEIGHT (Net Gross)	LAMP DIMENSIONS
GLL-CLW08-27W-BCA1-[xx]K	27 Watt	3,780 LM	blank = E26	[40]K = 4000K; [50]K = 5000K	0.62 lbs 0.84 lbs	6.88"H x 2.36"W
GLL-CLW08-36W-BCA1-[xx]K	36 Watt	5,040 LM	blank = E26	[40]K = 4000K; [50]K = 5000K	1.24 lbs 1.57 lbs	7.56"H x 3.35"W
GLL-CLW08-45W-BCA1-[xx]K	45 Watt	6,300 LM	blank = E26	[40]K = 4000K; [50]K = 5000K	1.54 lbs 1.87 lbs	9.1"H x 3.35"W
GLL-CLW08-45W-BCA1-[EX][xx]K	45 Watt	6,300 LM	[EX] = EX39	[40]K = 4000K; [50]K = 5000K	1.54 lbs 1.87 lbs	9.96"H x 3.35"W
GLL-CLW08-54W-BCA1-[xx]K	54 Watt	7,560 LM	blank = E26	[40]K = 4000K; [50]K = 5000K	1.54 lbs 1.87 lbs	9.1"H x 3.35"W
GLL-CLW08-54W-BCA1-[EX][xx]K	54 Watt	7,560 LM	[EX] = EX39	[40]K = 4000K; [50]K = 5000K	1.54 lbs 1.87 lbs	9.96"H x 3.35"W
GLL-CLW08-75W-BCA1-[EX][xx]K	75 Watt	10,500 LM	[EX] = EX39	[40]K = 4000K; [50]K = 5000K	3.26 lbs 3.52 lbs	9.96"H x 5.12"W
GLL-CLW08-100W-BCA1-[EX][xx]K	100 Watt	14,000 LM	[EX] = EX39	[40]K = 4000K; [50]K = 5000K	3.26 lbs 3.52 lbs	10.34"H x 5.12"W
GLL-CLW08-120W-BCA1-[EX][xx]K	120 Watt	16,800 LM	[EX] = EX39	[40]K = 4000K; [50]K = 5000K	3.41 lbs 3.63 lbs	11.26"H x 5.12"W

ORDERING GUIDE & EXAMPLE FOR STOCK INVENTORY: GLL-CLW08-75W-BCA1-EX40K

GLL = Green Lighting LED | CLW08 = Product Series | Wattage | B = Lumileds | C = Clear Lens | A1 = Version Number | Base | Color Temperature