




LED QUICK SHIP PROGRAM

LED MULTI PURPOSE FIXTURES



G11 SERIES



- 10KV Surge Protection.
- Increased 140 lm/watt efficacy.
- DM mounts compatible with round and square poles.



BEAM ANGLE	T3M
CERTIFICATIONS	cULus, DLC
CRI	>70
DIMMABLE	0-10V Dimming
OPERATING TEMP	-40°F~122°F
POWER FACTOR	>0.9
THD	≤20%
WATERPROOF	IP65 Wet Location

QUICK SHIP STOCK ORDERING

MODEL	WATT	LUMENS	VOLTAGE	BASE	CCT	WEIGHT (N G)	DIMENSIONS
GLL-G11-100W-CT3A1-BR10SPFM50	100 Watt	14,000 LM	A1 = 120~277V	FM = Trunnion	50 = 5000K	9.7 lbs 11.7 lbs	16.14"L x 12.83"W x 3.15"H
GLL-G11-100W-CT3A1-BR10SPAM50	100 Watt	14,000 LM	A1 = 120~277V	AM = Slip Fitter	50 = 5000K	10.14 lbs 12.12 lbs	19.1"L x 12.83"W x 3.15"H
GLL-G11-100W-CT3A1-BR10SPYM50	100 Watt	14,000 LM	A1 = 120~277V	YM = Yoke Mount	50 = 5000K	10.4 lbs 12.35 lbs	17.3"L x 12.83"W x 3.15"H
GLL-G11-100W-CT3A1-BR10SPDM50	100 Watt	14,000 LM	A1 = 120~277V	DM = Direct Mount	50 = 5000K	11.5 lbs 13.45 lbs	16.14"L x 12.83"W x 6.3"H
GLL-G11-150W-CT3[X1]-BR10SPFM50	150 Watt	21,000 LM	[A1] = 120~277V; [H1] = 277~480V	FM = Trunnion	50 = 5000K	10.36 lbs 12.35 lbs	16.14"L x 12.83"W x 3.15"H
GLL-G11-150W-CT3[X1]-BR10SPAM50	150 Watt	21,000 LM	[A1] = 120~277V; [H1] = 277~480V	AM = Slip Fitter	50 = 5000K	10.8 lbs 12.8 lbs	19.1"L x 12.83"W x 3.15"H
GLL-G11-150W-CT3[X1]-BR10SPYM50	150 Watt	21,000 LM	[A1] = 120~277V; [H1] = 277~480V	YM = Yoke Mount	50 = 5000K	11 lbs 13 lbs	17.3"L x 12.83"W x 3.15"H
GLL-G11-150W-CT3[X1]-BR10SPDM50	150 Watt	21,000 LM	[A1] = 120~277V; [H1] = 277~480V	DM = Direct Mount	50 = 5000K	12.13 lbs 14.1 lbs	20.7"L x 12.83"W x 6.3"H
GLL-G11-200W-CT3A1-BR10SPFM50	200 Watt	28,000 LM	A1 = 120~277V	FM = Trunnion	50 = 5000K	16.1 lbs 19.2 lbs	23.4"L x 12.9"W x 3.23"H
GLL-G11-200W-CT3A1-BR10SPAM50	200 Watt	28,000 LM	A1 = 120~277V	AM = Slip Fitter	50 = 5000K	15 lbs 18.1 lbs	26.85"L x 12.9"W x 3.23"H
GLL-G11-200W-CT3A1-BR10SPYM50	200 Watt	28,000 LM	A1 = 120~277V	YM = Yoke Mount	50 = 5000K	14.3 17.4 lbs	26.85"L x 12.9"W x 3.23"H
GLL-G11-200W-CT3A1-BR10SPDM50	200 Watt	28,000 LM	A1 = 120~277V	DM = Direct Mount	50 = 5000K	16.3 lbs 19.4 lbs	28.2"L x 12.9"W x 6.3"H
GLL-G11-300W-CT3[X1]-BR10SPFM50	300 Watt	42,000 LM	[A1] = 120~277V; [H1] = 277~480V	FM = Trunnion	50 = 5000K	17.9 lbs 20.9 lbs	23.4"L x 12.9"W x 3.23"H
GLL-G11-300W-CT3[X1]-BR10SPAM50	300 Watt	42,000 LM	[A1] = 120~277V; [H1] = 277~480V	AM = Slip Fitter	50 = 5000K	16.8 lbs 19.8 lbs	26.85"L x 12.9"W x 3.23"H
GLL-G11-300W-CT3[X1]-BR10SPYM50	300 Watt	42,000 LM	[A1] = 120~277V; [H1] = 277~480V	YM = Yoke Mount	50 = 5000K	17 lbs 19.2 lbs	6.85"L x 12.9"W x 3.23"H
GLL-G11-300W-CT3[X1]-BR10SPDM50	300 Watt	42,000 LM	[A1] = 120~277V; [H1] = 277~480V	DM = Direct Mount	50 = 5000K	18 lbs 21.2 lbs	28.2"L x 12.9"W x 6.3"H

ORDERING GUIDE & EXAMPLE FOR STOCK INVENTORY: GLL-G11-100W-CT3A1-BR10SPFM50

GLL = Green Lighting LED | G11/G07 = Product Series | Wattage | C = Seoul Diodes | T3M = Optics | A1 = 120~277V; H1 = 277~480V | BR = Bronze Housing

10SP = 10KV Surge Protection | Mounting | 50 = 5000K Color Temperature



- [PC] Photocell