



LED QUICK SHIP PROGRAM

LED WALL PACK FIXTURES



MINI



SWP03



SWP01



MINI, SWP03 & SWP01 SERIES



SPECIFICATIONS	
BEAM ANGLE	110°
CERTIFICATIONS	cULus, DLC
CRI	>80
DIMMABLE	0-10V Dimming
LED TYPE	SMD2835
INPUT VOLTAGE	100-277V; 50/60Hz
OPERATING TEMP	-40°F~122°F
POWER FACTOR	>0.9
SURGE PROTECTION	Yes
THD	≤20%
WARRANTY	6 Years
WATERPROOF	IP65 Wet Location

- Photocell standard with easy snap connection and disconnect on all models.
- DLC and cULus listed. Leading 6 year warranty.
- Minimum 130 lm/watt efficacy on all models.
- All models stocked in bronze color housing.

FIXTURE QUICK SHIP STOCK ORDERING

MODEL	WATTAGE	LUMENS	COLOR TEMP	WEIGHT (Net Gross)	DIMENSIONS
GLL-WP-MINIX1-20W-BF-BRP50	20 Watt	2,600 LM	50 = 5000K	2lbs 2.12lbs	2.9"L x 5.8"W x 8.6"H
GLL-SWP03-40BA1-BRP50	40 Watt	5,200 LM	50 = 5000K	4.1lbs 5.35 lbs	7.45"L x 8.5"W x 8.43"H
GLL-SWP03-60BA1-BRP50	60 Watt	7,800 LM	50 = 5000K	4.1lbs 5.35 lbs	7.45"L x 8.5"W x 8.43"H
GLL-SWP01-80WBA2-BRP50	80 Watt	10,400 LM	50 = 5000K	7.98 lbs 10.58 lbs	9.92"L x 14.21"W x 9.25"H
GLL-SWP01-120WBA2-BRP50	120 Watt	15,600 LM	50 = 5000K	9.7 lbs 12.35 lbs	9.92"L x 14.21"W x 9.25"H

ORDERING GUIDE & EXAMPLE FOR STOCK INVENTORY: GLL-SWP03-40BA1-BRP50

GLL = Green Lighting LED | Product Series | Wattage | B = Lumileds 2835 | X1/A1/A2 = Version number | BR = Bronze Housing | P = Photocell | 50 = 5000K